



COMMONWEALTH OF PENNSYLVANIA
DEPARTMENT OF ENVIRONMENTAL PROTECTION
OIL AND GAS MANAGEMENT PROGRAM

Well Record and Completion Report

DEP USE ONLY	
Site ID	Primary Fac ID
Client Id	Subfacility Id

Well Operator Range Resources - Appalachia, LLC		DEP ID# 141142	Well API # (Permit / Reg) 37125-23872		Project Number	Acres 1181
Address 380 Southpointe Blvd, Suite 300			Well Farm Name Goettel		Well # 9H	Serial #
City Canonsburg	State PA	Zip Code 15317	County Washington		Municipality Independence Twp	
Phone 724-743-6700	Fax 724-743-6790	USGS 7.5 min. quadrangle map West Middletown				

Check all that apply: Original Well Record Original Completion Report Amended Well Record Amended Completion Report

WELL RECORD Also complete the Log of Formations on back (page 2)

Well Type	<input checked="" type="checkbox"/> Gas	<input type="checkbox"/> Oil	<input type="checkbox"/> Combination Oil & Gas	<input type="checkbox"/> Injection	<input type="checkbox"/> Storage	<input type="checkbox"/> Disposal	
Drilling Method	<input type="checkbox"/> Rotary - Air	<input checked="" type="checkbox"/> Rotary - Mud	<input type="checkbox"/> Cable Tool				
Date Drilling Started 2/6/10	Date Drilling Completed 4/28/10	Surface Elevation 1318 ft.	Total Depth - Driller 11505 ft.	Total Depth - Logger 11505 ft.			
Casing and Tubing		Cement returned on surface casing? <input checked="" type="checkbox"/> Yes <input type="checkbox"/> No		Cement returned on coal protective casing? <input type="checkbox"/> Yes <input type="checkbox"/> No <input checked="" type="checkbox"/> N/A			
Hole Size	Pipe Size	Wt.	Thread / Weld	Amount in Well (ft)	Material Behind Pipe Type and Amount	Packer / Hardware / Centralizers Type Size Depth	Date Run
30"	26"	108#	Thread	40'	Driven	-- 26" 40'	2/6/10
24"	20"	81.3#	Thread	296'	Gas Block, 330 sx	GS 20" 296'	2/17/10
12-1/4"	9/5/8"	40#	Thread	1888'	Gas Block, 920 sx	GS 9-5/8" 1888'	3/17/10
8-3/4"	5-1/2"	20#	Thread	11505'	50/50 12% poz, 816 sx	FS 5-1/2" 11505'	4/28/10
					50/50 13% poz, 722 sx		
					Acid sol 595 sx		

COMPLETION REPORT

Perforation Record			Stimulation Record							
Date	Interval Perforated From	To	Date	Interval Treated	Fluid Type	Amount	Propping Agent Type	Amount	Average Injection Rate	
8/9/10	7,860' MD	11,360' MD	8/24/10	Marcellus Shale	Slick H2O	105,818 bbl	Sand	6,025k lbs	63.6 bpm	
Natural Open Flow			too small to determine		Natural Rock Pressure		too small		Hours	Days
After Treatment Open Flow			Not enough time to determine		After Treatment Rock Pressure		Undeterminable		Hours	Days

Well Service Companies -- Provide the name, address, and phone number of all well service companies involved.

Name Patterson UTI	Name Universal Well Services	Name Frac Tech Services
Address 4501 Lamesa Highway	Address 730 Braddock View Dr	Address 16858 IH20
City - State - Zip Snyder, TX 79549	City - State - Zip Mt. Braddock, PA 15465	City - State - Zip Cisco, TX 76437
Phone 325-574-6300	Phone 724-430-6201	Phone 817-850-1008

LOG OF FORMATIONS

Well API#: 37-125-23872-_____

(If you will need more space than this page, please photocopy the blank form before filling it in.)

Formation Name or Type	Top (feet)	Bottom (feet)	Gas at (feet)	Oil at (feet)	Water at (fresh / brine; ft.)	Source of Data
Fill	0'	50'				Drillers Log
Sand	50'	110'				Drillers Log
Shale	110'	150'				Drillers Log
Sand	150'	180'				Drillers Log
Sand and Shale	180'	360'				Drillers Log
Shale	360'	420'				Drillers Log
Sand	420'	440'				Drillers Log
Shale	440'	450'				Drillers Log
Sand and Shale	450'	860'				Drillers Log
Shale	860'	1030'				Drillers Log
Sand and Shale	1030'	1110'				Drillers Log
Sand	1110'	1140'				Drillers Log
Shale	1140'	1310'				Drillers Log
Sand and Shale	1310'	1580'				Drillers Log
Sand	1580'	1610'				Drillers Log
Shale	1610'	2285'				Drillers Log
Sand	2285'	2360'				Drillers Log
Sand and Shale	2360'	2780'				Drillers Log
Shale	2780'	3320'				Drillers Log
Sand and Shale	3320'	3580'				Drillers Log
Shale	3580'	3630'				Drillers Log
Sand and Shale	3630'	4240'				Drillers Log
Sand	4240'	4270'				Drillers Log
Sand and Shale	4270'	4595'				Drillers Log
Shale	4595'	4780'				Drillers Log
Sand	4780'	4810'				Drillers Log
Shale	4810'	5120'				Drillers Log
Sand and Shale	5120'	5245'				Drillers Log
Shale	5245'	5680'				Drillers Log
Sand and Shale	5680'	5710'				Drillers Log
Shale	5710'	6000'				Drillers Log
Horizontal						
Shale	4850'	7170'				Drillers Log
Limestone	7170'	7490'				Drillers Log
Shale	7490'					Drillers Log
Drillers Total Depth		11505'				Drillers Log

I do hereby certify to the best of my knowledge, information and belief that the well identified on this Well Record and Completion Report has been properly cased and cemented in accordance with the requirements of 25 Pa. Code Chapter 78 and any conditions contained in the permit for this well. I am aware that there are significant penalties for submitting false information, including the possibility of fine and imprisonment.

Well Operator's Signature	DEP USE ONLY
	Reviewed by: _____ Date: _____
Title: _____ Date: _____	Comments: _____
Michael Hurey-Completions Engineer 9/9/10	




RANGE RESOURCES

Goettel Unit #9H
Well API: 37-125-23872

Completion Date: August 9 - 24, 2010
Township: Independence

% Composition of Hydraulic Fracture Fluid (by volume)						
Product Name	Additive	Purpose	Use and Dillution	Volume	Overall %	Common Uses
Water	Carrier Fluid	Creates fracture network in shale and carry proppant to the formation	Primary constituent	4,444,339 gal	94.13%	Water is the most abundant molecule on the Earth's surface
Sand	Sand	Allows fractures to remain open so gas can escape	Second most common constituent, making up almost 6% of the fluid	272,324 gal	5.77%	Drinking water filtration, play sand
FRW-200	Friction Reducer	Reduces friction between fluid and pipe	Diluted at one-half gallon per 1,000 gallons of water	1,791 gal	0.04%	Water treatment; soil conditioner; some children's toys
MC B-8642/Bioban	Antimicrobial Agent	Eliminates bacteria in the water that produce corrosive byproducts	Diluted at one-half gallon per 1,000 gallons of water	1,254 gal	0.03%	Water treatment, disinfectant; sterilize medical and dental equipment and surfaces
MX 588-2	Scale Inhibitor	Prevents scaling in pipe	Diluted at one-tenth gallon per 1,000 gallons of water	440 gal	0.01%	Water treatment, household cleaners, de-icing agent
HCL Acid	Perf Clean-Up	Dissolves cement and minerals to help initiate fractures	139 gallons per stage (non-diluted chemicals)	1282 gal	0.03%	Swimming pool and household cleaner

Composition of Hydraulic Fracture Fluid (by volume)





Composition of Components in Marcellus Shale Hydraulic Fracturing Fluid

RANGE RESOURCES

Common Name & Supplier	Supplier Chemical Name	Common Description	Hazardous Component listed on MSDS	Purpose	MSDS Component Weight % of Chemical	Gallons MSDS Component in Well	Maximum Concentration of MSDS Component of Total Stage Fluid		
							% Vol	% Weight	
7.5% HCl Mixture (FracTech)	37% HCL	concentrated HCl Acid	HCL	Cleans perforation	37.0%	1281.62	0.0271%	0.0109%	
	CI-100	Corrosion Inhibitor	Methanol	Protects casing	95.0%	39.20	0.0008%	0.0006%	
			Propargyl Alcohol	Protects casing	5.0%	1.68	0.0000%	0.0000%	
	NE100	Non- Emulsifer	No hazardous ingredients	Prevents emulsions	0.0%	N/A	N/A	N/A	
FE100L	Iron Chelator	No hazardous ingredients	Prevents precipitation	0.0%	N/A	N/A	N/A	N/A	
TOTAL								0.0280%	0.0115%

Friction Reducer (FracTech)	FRW-200	Friction Reducer	No hazardous ingredients	Reduce friction down casing	0.0%	N/A	N/A	N/A
------------------------------------	---------	------------------	--------------------------	-----------------------------	------	-----	-----	-----

Scale Inhibitor (Multichem)	MC MS S-2510T	Scale Inhibitor	Sodium hydroxide	prevents scale deposits in pipe and perforations	5.0%	16.10	0.0003%	0.0005%	
			Ethylene Glycol		60.0%	261.66	0.0055%	0.0057%	
TOTAL								0.0059%	0.0062%

Antibacterial Agent (Multichem)	Bioban	Antibacterial Agent	4,4-Dimethyloxazolidine	eliminates bacteria in water	78.0%	688.98	0.0146%	0.0134%	
			3,4,4-Trimethyloxazolidine		5.0%	45.10	0.0010%	0.0009%	
			2-Amino-2-methyl-1-propanol		1.0%	9.45	0.0002%	0.0002%	
			Formaldehyde Amine		0.5%	4.11	0.0001%	0.0001%	
	BMC B-8642	Antibacterial Agent	Glutaraldehyde	eliminates bacteria in water	60.0%	155.24	0.0033%	0.0045%	
			n-alkyl dimethyl benzyl ammonium chloride		10.0%	25.87	0.0005%	0.0008%	
			Ethanol		1.0%	2.59	0.0001%	0.0001%	
TOTAL								0.0158%	0.0145%

SUMMARY	by vol %	by weight %
	0.050%	0.032%